

Versati Air-to-water Monobloc Heat Pump



Model		WAWG3-16HDM/C
Max Heating Capacity*	BTU/h	61000
Min Heating Capacity*	BTU/h	23204
Max Cooling Capacity**	BTU/h	46000
Min Cooling Capacity**	BTU/h	17915
normal Heating Capacity	BTU/h	51186
normal Cooling Capacity	BTU/h	42655
COP*		UP to 4.4
EER**		UP to 11.8
Max Running Amps	A	60
Compressor Rating Load	A	28
Electric Heater Minimum Circuit Ampacity	A	32
Whole Unit Max Fuser Or Circuit Breaker	A	60
Electric Heater Max Fuser Or Circuit Breaker	A	35
Power Supply		208/230/1N-60HZ
Compressor Quantity		1
Compressor Model		2-stage Inverter Compressor
Fan Quantity		1
Rated input current of fan motor		1.7A
Fan Rotate Speed	RPM	100~900
Sound Power Level***	dB(A)	59
Space Heating: Operation Temp Range		-13 to 95°F (-25 to 35°C)
Space Cooling: Operation Temp Range		5 to 118°F (-15 to 48°C)
Water Connection	in.	1 1/3
Water Flow Voume	GPM	8.65
Unit Net Dimension	in(L/W/H)	47 1/2*17 1/2*34 4/7
Unit Shipping Dimension	in(L/W/H)	52 2/3*21 7/9*40 1/6
Net Weight	lb.	328
Shipping Weight	lb.	357
Heating Test Condition:* Amb 47°F/8.3°C,LWT:105°F/40.6°C		
Cooling Test Condition:** Amb 95°F/35°C,EWT 54°F/12.2°C, LWT:44°F/6.7°C		
Sound Test Condition:***Amb95°F/35°C,EWT 53.6°F/12°C, LWT:44.6°F/7°C		